

Over **Track**

4,5W / 350lm / 2700K / On/Off / Medium 41° / ø85mm

60268




Design: O/M + Bartenbach GmbH Track-mounted spotlight with die-cast aluminium body with electrostatic 100% polyester paint finish. Spot-lens with individual complex surface rips to provide a focal light and an extremely narrow beam. Orientable by 90° horizontal rotation and 330° vertical rotation.

Driver included.

LED CRI>90 / >50.000h, L80/B10 2-step MacAdam / Driver included. IP20 | 230Vac | 50/60Hz




Power 4,5W 5,8W Flux 480Im 350Im Efficiency 107Im/W 61Im/W LOR - 73% Operating Condition - 230Vac	● 2700K	Light Source	Luminaire
Efficiency 107lm/W 61lm/W LOR - 73%	Power	4,5W	5,8W
LOR - 73%	Flux	480lm	350lm
	Efficiency	107lm/W	61lm/W
Operating Condition - 230Vac	LOR	-	73%
	Operating Condition	-	230Vac



Beam angle Medium 41° Application Weight 0,64Kg

mm



Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F Model Identifier 2053560245L