

10W / 810lm / 3000K / On/Off / Medium 28°
/ ø45mm

60297



Design: O/M
Recessed adjustable spotlight with aluminium body.
The spotlight can be rotated up to 90° horizontally and 330° vertically.
Easy recessing system with spring clips.
Accessories available separately and easily applicable after installation.

LED CRI>90 / >50.000h, L80/B10
2-step MacAdam / Power supply included.
IP20 | 230Vac | 50/60Hz



3000K

Light Source

Luminaire


Power 10W 12,5W

Flux 1035lm 810lm

Efficiency 119lm/W 73lm/W

LOR - 78%

UGR - <16



Beam angle
Medium 28°




Weight
0,6Kg

□ mm

194x26

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005



Optional

- 59016 Elliptical refractor Ø39x0,5mm
- 59017 Soft diffuser Ø39x0,5mm
- 59018 Louvre Ø39x3mm
- 59019 Snoot 72mm Ø45x72

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU

supplemented by 2021/340/EU Energy Consumption Labelling

Ordinance. This product contains a light source of efficiency class F

Model Identifier 2053560257H