


Onit Track (230v)

10W / 780Im / 2700K / DALI / Spot 12° / ø45mm

installation on three-phase track.

60318



The spotlight can be rotated up to 90° horizontally and 330° vertically.

Adjustable spotlight with aluminium body for


Accessories available separately and easily applicable after installation.

LED CRI>90 / >50.000h, L80/B10 2-step MacAdam / Power supply included. IP20 | 230Vac | 50/60Hz



Design: O/M

2700K	Light Source	Luminaire
Power	10W	12,5W
Flux	955lm	780lm
Efficiency	96lm/W	62lm/W
LOR	-	0.82
UGR	-	<13




Beam angle Spot 12°

Application



Weight

nm.



Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

Optional

59016 Elliptical refractor

Ø39x0.5mm 59017 Soft diffuser

Ø39x0,5mm

59018 Louvre

Ø39x3mm **59019** Snoot 72mm

Ø45×72

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F Model Identifier 2053560245H