




Design: O/M


Ceiling-recessed luminaire made of aluminium die-cast.


Recessing accessory for flush version supplied separately.

LED CRI>90 / >50.000h, L80/B10  
2-step MacAdam / power supply included  
IP54 | 230Vac | 50/60Hz



 <b>3000K</b>	<b>Light Source</b>	<b>Luminaire</b>
<b>Power</b>	<b>10W</b>	<b>12,5W</b>
<b>Flux</b>	<b>1035lm</b>	<b>750lm</b>
<b>Efficiency</b>	<b>104lm/W</b>	<b>60lm/W</b>
<b>LOR</b>	<b>-</b>	<b>72%</b>
<b>UGR</b>	<b>-</b>	<b>&lt;22</b>



<b>Beam angle</b> <b>Flood 37°</b>
<b>Application</b> 
<b>Weight</b> <b>0,38Kg</b>



Ø70 (trim version)



### Finishes

- .04 Matt White
- .05 Matt Black

### Optional

- 59063** Flush accessory (12.5mm ceilings)  
176x17mm
- 59064** Flush accessory (15mm ceilings)  
176x19,5mm
- 59065** Flush accessory (25mm ceilings)  
176x29,5mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

### Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class F  
Model Identifier 2053560257H