

53W / 5500lm / 3000K / DALI / Wide flood  
76° / 2933mm

60493

Product timing available by request




Design: OM + Bartenbach GmbH  
Recessed luminaire with housing made of aluminium with 25 micron maximum corrosion resistance anodization in matte finish or electrostatic 100% polyester paint with textured finish.  
Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.  
Linear lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.  
Fitting accessories ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz



LED	3000K	Light Source	Luminaire
Power		53W	62,4W
Flux		6900lm	5500lm
Efficiency		130lm/W	88lm/W
LOR		-	80%
UGR		-	<19



Beam angle  
Wide flood 76°


Application



Weight  
4,7Kg



47x2923



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Mandatory

51027 Recessed fitting accessory

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com

O/M recommends that any false ceilings intended for recessed products should be installed only after the products to be used have been chosen. The same applies when preparing openings for this type of product. O/M recommends reinforcing false ceilings close to any such openings, in accordance with the characteristics of the product to be recessed. The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com