

inFinit Pendant direct/indirect

27+56W / 2880+2720lm / 4000K / DALI / Wide flood 76° / batwing / 2344mm

60543

Product timing available by request

Design: OM + Bartenbach GmbH Pendant direct and indirect luminaire with housing made of aluminium in matte finish.

Aluminium anodised end caps with matt finish. Linear lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.


Indirect light: Lenses for batwing effect protected by a transparent polycarbonate diffuser. Fitting accessories ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam Power supply included. IP20 | 230Vac | 50/60Hz



1000K	Light Source	Luminaire	
Power	27+56W	32+64W	
Flux	3600+3440lm	2880+2720lm	
Efficiency	85lm/W	57lm/W	
LOR	-	80%	
UGR	-	<19	

-45-



Beam angle Wide flood 76° / batwing

Application



Weight 8,2Kg

-ir	nis	he	es


ø60x35mm

O .04 Matt White

.05 Matt Black

Mandatory 59054 Pendant direct/indirect fitting accessory 56051 Clear Base DALI

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com



2344

mm