

Uw Recessed

16W / 740Im / 3000K / On/Off / Wallwasher / 615mm

60568



Design: OM + Bartenbach GmbH Recessed luminaire with housing made of aluminium with 25 micron maximum corrosion resistance anodization in matte finish or electrostatic 100% polyester paint with textured finish.

Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-

Linear extruded lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.


Fitting accessories ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam Power supply included. IP20 | 230Vac | 50/60Hz





100 3000K	Light Source	Luminaire
Power	16W	19,5W
Flux	1600lm	740lm
Efficiency	100lm/W	38lm/W
LOR	-	46%
UGR	-	-







Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

.10 Anodised aluminium

51027 Recessed fitting acessory

O/M recommends that any false ceilings intended for recessed products should be installed only after the products to be used have been chosen. The same applies when preparing openings for this type $% \left\{ \left(1\right) \right\} =\left\{ \left(1\right) \right\} =$ of product. O/M recommends reinforcing false ceilings close to any such openings, in accordance with the characteristics of the product to be recessed. The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com