

U45 Surface/Pendant

20W / 1775lm / 4000K / On/Off / Diffuse / 1429mm

61133



Design: Eduardo Souto de Moura Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint. Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.


Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with texturedfinish.

Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP40 | 230Vac | 50/60Hz



1000K	Light Source	Luminaire
Power	20W	24,4W
Flux	3775lm	1775lm
Efficiency	189lm/W	73lm/W
LOR	-	47%
UGR	-	<25



Beam angle Diffuse Application Weight

2,3Kg

1429

Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

.10 Anodised aluminium

Mandatory

54036 Pendant direct fitting acessory 54034 Clear Base ø60x35mm

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C Model Identifier 89603212, 89603217

mm