


27W / 2300lm / 2700K / On/Off / Diffuse /
1143mm

61513



Design: Eduardo Souto de Moura
 Recessed trimless luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.
 Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.
 Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.
 Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
 Power supply included.
 IP42 | 230Vac | 50/60Hz



LED 2700K

Light Source Luminaire


Power 27W 32,9W

Flux 4780lm 2300lm

Efficiency 177lm/W 70lm/W

LOR - 48%

UGR - <25



Beam angle
Diffuse

Application



Weight
2,5Kg

mm

62x1145


Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium

Mandatory

59024 Recessed trimless fitting accessory

O/M recommends that any false ceilings intended for recessed products should be installed only after the products to be used have been chosen. The same applies when preparing openings for this type of product. O/M recommends reinforcing false ceilings close to any such openings, in accordance with the characteristics of the product to be recessed. The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com



Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
 supplemented by 2021/340/EU Energy Consumption Labelling
 Ordinance. This product contains light sources of efficiency class D
 Model Identifier 89603215