

## **U60** Surface/Pendant

54W / 5000lm / 4000K / On/Off / Diffuse / 2271mm

61597



Design: Eduardo Souto de Moura Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint. Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.


Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with texturedfinish.

Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP40 | 230Vac | 50/60Hz



1000K	Light Source	Luminaire
Power	54W	63,5W
Flux	10400lm	5000lm
Efficiency	193lm/W	79lm/W
LOR	-	48%
UGR	-	<25



Beam angle Diffuse Application Weight

mm



## Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

.10 Anodised aluminium

## Mandatory

54036 Pendant direct fitting acessory 54034 Clear Base ø60x35mm

## Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C Model Identifier 89603217