U60
IP54 Recessed

27W / 2340lm / 3000K / DALI / Diffuse / 1153mm

61633

Design: Eduardo Souto de Moura
Recessed luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.
Frosted polycarbonate diffuser with user friendly clipping system.
Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.
Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP54 | 230Vac | 50/60Hz

LED 3000K	Light Source	Luminaire
Power	**27W**	**32,9W**
Flux	**4900lm**	**2340lm**
Efficiency	**181lm/W**	**71lm/W**
LOR	**-**	**48%**
UGR	**-**	**<25**



Beam angle
Diffuse

Application

Weight
2,5Kg

mm

62x1143



Finishes

- ○ **.01** White / RAL 9010
- ● **.02** Black / RAL 9005
- ◍ **.10** Anodised aluminium

Mandatory
52106 Recessed fitting acessory

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com
O/M recommends that any false ceilings intended for recessed products should be installed only after the products to be used have been chosen. The same applies when preparing openings for this type of product. O/M recommends reinforcing false ceilings close to any such openings, in accordance with the characteristics of the product to be recessed. The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations
2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C
Model Identifier 89603216

www.om-light.com / mail@om-light.com Rua Maurício Lourenço Oliveira 186, 4405-034 Vila Nova de Gaia, Porto. Portugal. / Apartado 1538 4401-901 Vila Nova de Gaia, Porto Portugal / tel. +351 223 710 419