

## **U60 IP54 Surface**

32W / 2680lm / 2700K / On/Off / Diffuse / 2271mm

61708



Design: Eduardo Souto de Moura Surface luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.

Frosted polycarbonate diffuser with user friendly clipping system.

Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with texturedfinish.


Fitting accessories not included.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP54 | 230Vac | 50/60Hz



₩ (€

<b>●</b> 2700K	Light Source	Luminaire	
Power	32W	37,6W	
Flux	5600lm	2680lm	
Efficiency	175lm/W	71lm/W	
LOR	-	48%	
UGR	-	<25	



Beam angle Diffuse Application

Weight

mm



## Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

.10 Anodised aluminium

## Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class D Model Identifier 89603215