

68W / 5750lm / 2700K / DALI / Diffuse /
2831mm

61719



Design: Eduardo Souto de Moura
 Surface luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.
 Frosted polycarbonate diffuser with user friendly clipping system.
 Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.
 Fitting accessories not included.


LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
 Power supply included.
 IP54 | 230Vac | 50/60Hz



2700K

Light Source Luminaire

Power	68W	80W
Flux	11950lm	5750lm
Efficiency	176lm/W	72lm/W
LOR	-	48%
UGR	-	<25



Beam angle
Diffuse



Weight
6,2Kg

mm

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium

For the specific supply of "DALI 2" drivers, please contact:
 support@om-light.com



Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
 supplemented by 2021/340/EU Energy Consumption Labelling
 Ordinance. This product contains light sources of efficiency class C
 and D
 Model Identifier 89603210, 89603215