

54W / 4680lm / 3000K / On/Off / Diffuse /  
2271mm

61725



Design: Eduardo Souto de Moura  
Surface luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.  
Frosted polycarbonate diffuser with user friendly clipping system.  
Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.  
Fitting accessories not included.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP54 | 230Vac | 50/60Hz



**3000K**

**Light Source** **Luminaire**


**Power** **54W** **63,5W**

**Flux** **9800lm** **4680lm**

**Efficiency** **181lm/W** **74lm/W**

**LOR** **-** **48%**

**UGR** **-** **<25**



**Beam angle**  
**Diffuse**



**Weight**  
**5Kg**

mm

**Finishes**

- .01 White / RAL 9010**
- .02 Black / RAL 9005**
- .10 Anodised aluminium**

Data according to regulations  
2019/2020/EU supplemented by 2021/341 |2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains light sources of efficiency class C  
Model Identifier 89603216

