

U60 IP54 Surface

40W / 3450lm / 3000K / On/Off / Diffuse / 2831mm

61726



Design: Eduardo Souto de Moura Surface luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.

Frosted polycarbonate diffuser with user friendly clipping system.

Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with texturedfinish.


Fitting accessories not included.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP54 | 230Vac | 50/60Hz



₩ (€

● 3000K	Light Source	Luminaire
Power	40W	47,1W
Flux	7150lm	3450lm
Efficiency	179Im/W	73lm/W
LOR	-	48%
UGR	-	<25



Beam angle Diffuse Application Weight 6,2Kg

mm

Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

.10 Anodised aluminium

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C Model Identifier 89603211, 89603216

