

U60 Surface/Pendant

54W / 6080lm / 3000K / On/Off / Prismatic / 2271mm

61869



Design: Eduardo Souto de Moura Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint. Prismatic polycarbonate diffuser with low luminance and glare control (UGR<19 for low output or UGR<22 for High Output).


Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with texturedfinish.

Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP40 | 230Vac | 50/60Hz



| 3000K | Light Source | Luminaire |
|------------|--------------|-----------|
| Power | 54W | 63,5W |
| Flux | 9800lm | 6080lm |
| Efficiency | 181lm/W | 96lm/W |
| LOR | - | 62% |
| UGR | - | <22 |
| | | |



Beam angle Prismatic Application

Weight

| - 1 | -4 | |
|-----|-----|----|
| - 1 | - 1 | mm |



Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005 .10 Anodised aluminium

Mandatory

54036 Pendant direct fitting acessory 54034 Clear Base

ø60x35mm

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C Model Identifier 89603216