

## **U60** Surface/Pendant

68W / 7600Im / 3000K / On/Off / Prismatic / 2831mm

61871



Design: Eduardo Souto de Moura Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint. Prismatic polycarbonate diffuser with low luminance and glare control (UGR<19 for low output or UGR<22 for High Output).


Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with texturedfinish.

Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP40 | 230Vac | 50/60Hz



| 1000K      | Light Source | Luminaire |
|------------|--------------|-----------|
| Power      | 68W          | 80W       |
| Flux       | 12250lm      | 7600lm    |
| Efficiency | 180lm/W      | 95lm/W    |
| LOR        | -            | 62%       |
| UGR        | -            | <22       |
|            |              |           |



Beam angle Prismatic Application

Weight 6,2Kg

mm



| 0/M | 1   |
|-----|-----|
|     | 85  |
|     | ] + |

## Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005 .10 Anodised aluminium

Mandatory

54036 Pendant direct fitting acessory 54034 Clear Base

ø60x35mm

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C Model Identifier 89603211, 89603216