

## **U60** Surface/Pendant

14W / 1520lm / 3000K / DALI / Prismatic / 1149mm

61872



Design: Eduardo Souto de Moura Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint. Prismatic polycarbonate diffuser with low luminance and glare control (UGR<19 for low output or UGR<22 for High Output).


Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with texturedfinish.

Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP40 | 230Vac | 50/60Hz



3000K	Light Source	Luminaire
Power	14W	17,1W
Flux	2450lm	1520lm
Efficiency	175lm/W	89lm/W
LOR	-	62%
UGR	-	<19



Beam angle Prismatic Application

Weight

mm





## Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

.10 Anodised aluminium

## Mandatory

54036 Pendant direct fitting acessory 56051 Clear Base DALI ø60x35mm

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

Data according to regulations 2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C Model Identifier 89603216