

174W / 14500lm / 3000K / DALI / Diffuse /  
2891mm

62039



Design: Eduardo Souto de Moura  
 Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.  
 Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.  
 Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.  
 Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
 Power supply included.  
 IP40 | 230Vac | 50/60Hz



**LED** 3000K

**Light Source** Luminaire


**Power** 174W 201W

**Flux** 23500lm 14500lm

**Efficiency** 134lm/W 72lm/W

**LOR** - 62%

**UGR** - <25



**Beam angle**  
**Diffuse**

**Application**

**Weight**  
**12,9Kg**

**Image not found or type unknown**

**Finishes**

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium

**Mandatory**

54036 Pendant direct fitting accessory

56051 Clear Base DALI

ø60x35mm

For the specific supply of "DALI 2" drivers, please contact:  
[support@om-light.com](mailto:support@om-light.com)

**Data according to regulations**

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
 supplemented by 2021/340/EU Energy Consumption Labelling  
 Ordinance. This product contains light sources of efficiency class D  
 Model Identifier WU-M-526-S-BC-830, WU-M-536-S-BC-830