

## **U120** Surface/Pendant

76W / 6640Im / 4000K / On/Off / Diffuse / 2319mm

62044



Design: Eduardo Souto de Moura Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint. Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.


Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with texturedfinish.

Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP40 | 230Vac | 50/60Hz



1000K	Light Source	Luminaire
Power	76W	89,4W
Flux	10720lm	6640lm
Efficiency	141lm/W	74lm/W
LOR	-	62%
UGR	-	<25



Beam angle Diffuse Application Weight

10,4Kg

mm



Finishes

O .01 White / RAL 9010 ● .02 Black / RAL 9005

.10 Anodised aluminium

Mandatory

54036 Pendant direct fitting acessory

**54034** Clear Base

ø60x35mm

Data according to regulations 2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C Model Identifier WU-M-536-S-BC-840