

## **U120** Surface/Pendant

95W / 8300lm / 4000K / DALI / Diffuse / 2891mm

62054



Design: Eduardo Souto de Moura Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint. Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.


Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with texturedfinish.

Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP40 | 230Vac | 50/60Hz



( 4000K	Light Source	Luminaire
Power	95W	109W
Flux	13400lm	8300lm
Efficiency	141lm/W	76lm/W
LOR	-	62%
UGR	-	<25



Beam angle Diffuse Application Weight

12,9Kg

## Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

.10 Anodised aluminium

## Mandatory

54036 Pendant direct fitting acessory 56051 Clear Base DALI ø60x35mm

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

Data according to regulations 2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C Model Identifier WU-M-526-S-BC-840, WU-M-536-S-BC-840

