


U120 IP54 Recessed

140W / 11600lm / 3000K / On/Off / Diffuse / 2323mm

62061



Design: Eduardo Souto de Moura

Recessed luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.

Frosted polycarbonate diffuser with user friendly clipping system.

Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-


Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP54 | 230Vac | 50/60Hz



₩ (€

1000K	Light Source	Luminaire
Power	140W	161W
Flux	18800lm	11600lm
Efficiency	134lm/W	72lm/W
LOR	-	62%
UGR	-	<25



Beam angle Diffuse Application

Weight 10,4Kg

□ mm	/ ₄ 7122x2313	



Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

.10 Anodised aluminium

Mandatory

53080 Recessed fitting acessory

O/M recommends that any false ceilings intended for recessed products should be installed only after the products to be used have been chosen. The same applies when preparing openings for this type of product. O/M recommends reinforcing false ceilings close to any such openings, in accordance with the characteristics of the product to be recessed. The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class D Model Identifier WU-M-536-S-BC-830