


95W / 7000lm / 3000K / On/Off / Diffuse /  
2895mm

62062



Design: Eduardo Souto de Moura  
 Recessed luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.  
 Frosted polycarbonate diffuser with user friendly clipping system.  
 Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.  
 Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
 Power supply included.  
 IP54 | 230Vac | 50/60Hz



LED 3000K

Light Source Luminaire


Power 95W 109W

Flux 11300lm 7000lm

Efficiency 119lm/W 64lm/W

LOR - 62%

UGR - &lt;25

Beam angle  
Diffuse

Application

Weight  
13Kg

mm

122x2885


Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium

Mandatory

53080 Recessed fitting accessory

O/M recommends that any false ceilings intended for recessed products should be installed only after the products to be used have been chosen. The same applies when preparing openings for this type of product. O/M recommends reinforcing false ceilings close to any such openings, in accordance with the characteristics of the product to be recessed. The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com



Data according to regulations  
 2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
 supplemented by 2021/340/EU Energy Consumption Labelling  
 Ordinance. This product contains light sources of efficiency class D  
 Model Identifier WU-M-526-S-BC-830, WU-M-536-S-BC-830