

38W / 2800lm / 3000K / On/Off / Diffuse /  
1173mm

62088



Design: Eduardo Souto de Moura  
 Surface luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.  
 Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.  
 Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
 Power supply included.  
 IP54 | 230Vac | 50/60Hz



**3000K**

**Light Source** **Luminaire**


**Power** **38W** **44,7W**

**Flux** **4520lm** **2800lm**

**Efficiency** **119lm/W** **63lm/W**

**LOR** **-** **62%**

**UGR** **-** **<25**



**Beam angle**  
**Diffuse**



**Weight**  
**5,2Kg**

**mm**

**Finishes**

- .01 White / RAL 9010**
- .02 Black / RAL 9005**
- .10 Anodised aluminium**

Data according to regulations  
 2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
 supplemented by 2021/340/EU Energy Consumption Labelling  
 Ordinance. This product contains light sources of efficiency class D  
 Model Identifier WU-M-536-S-BC-830

