

U120 IP54 Surface

76W / 5600lm / 3000K / DALI / Diffuse / 2319mm

62100



Design: Eduardo Souto de Moura Surface luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.

Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.


Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with texturedfinish.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP54 | 230Vac | 50/60Hz



₩ (€

| 3000K | Light Source | Luminaire |
|--------------|--------------|-----------|
| Power | 76W | 89,4W |
| Flux | 9040lm | 5600lm |
| Efficiency | 119lm/W | 63lm/W |
| LOR | - | 62% |
| UGR | - | <25 |
| | | |



Beam angle Diffuse Application

Weight 10,4Kg

mm

Finishes O .01 White / RAL 9010 ● .02 Black / RAL 9005

.10 Anodised aluminium

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

Data according to regulations 2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class D Model Identifier WU-M-536-S-BC-830

2319