

U120 IP54 Surface

140W / 11600lm / 3000K / DALI / Diffuse / 2319mm

62101



Design: Eduardo Souto de Moura Surface luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.


Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.

Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with texturedfinish.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP54 | 230Vac | 50/60Hz



3000K	Light Source	Luminaire
Power	140W	161W
Flux	18800lm	11600lm
Efficiency	134lm/W	72lm/W
LOR	-	62%
UGR	-	<25



Beam angle Diffuse Application

Weight 10,4Kg

mm

2319



Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

.10 Anodised aluminium

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class D Model Identifier WU-M-536-S-BC-830