

## **U120 IP54 Surface**

38W / 3320lm / 4000K / DALI / Diffuse / 1173mm

62112



Design: Eduardo Souto de Moura Surface luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.

Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.


Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with texturedfinish.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP54 | 230Vac | 50/60Hz



₩ (€

| 1000K      | Light Source | Luminaire |
|------------|--------------|-----------|
| Power      | 38W          | 44,7W     |
| Flux       | 5360lm       | 3320lm    |
| Efficiency | 141im/W      | 74lm/W    |
| LOR        | -            | 62%       |
| UGR        | -            | <25       |
|            |              |           |



Beam angle Diffuse Application Weight

mm

O .01 White / RAL 9010 ● .02 Black / RAL 9005

Finishes

.10 Anodised aluminium

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

1173

Data according to regulations 2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C Model Identifier WU-M-536-S-BC-840