


35W / 3100lm / 4000K / On/Off / Diffuse /  
571mm

62145



**Structure**  
1 Profile  
2 End caps  
3 Fitting accessories  
4 Profile coupling

**Diffuser**  
A Polycarbonate frost diffuser  
**Light Source**  
B LED Modules

Design: O/M  
LED light source with good colour consistency and long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz




4000K

**Light Source**


**Luminaire**

<b>Power</b>	<b>35W</b>	<b>41,2W</b>
<b>Flux</b>	<b>5000lm</b>	<b>3100lm</b>
<b>Efficiency</b>	<b>143lm/W</b>	<b>75lm/W</b>
<b>LOR</b>	<b>-</b>	<b>62%</b>
<b>UGR</b>	<b>-</b>	<b>&lt;25</b>



**Beam angle**  
**Diffuse**

**Application**



**Weight**  
**0,5Kg**

mm

**Finishes**

Choose the length and layout of the system exactly as you want it, to model the right lighting functions for different tasks. For further information please contact: support@om-light.com

**Data according to regulations**

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class C  
Model Identifier WU-M-536-S-BC-840

