


41+30W / 3450+2070lm / 3000K / On/Off /  
Diffuse / batwing / 1679mm

62307



## Structure

- 1 Profile
- 2 End caps
- 3 Fitting accessories
- 4 Profile coupling

## Diffuser

- A Polycarbonate frost diffuser

## Light Source

- B LED Modules

Design: O/M

LED light source with good colour consistency and long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz

LED 3000K

## Light Source

## Luminaire


Power 41+30W 48,2+36,6W

Flux 7350+3300lm 3450+2070lm

Efficiency 150lm/W 65lm/W

LOR - 52%

UGR - &lt;25

Beam angle  
Diffuse / batwing

## Application

Weight  
0,57Kg

mm

## Finishes

Choose the length and layout of the system exactly as you want it, to model the right lighting functions for different tasks. For further information please contact: support@om-light.com

## Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains light sources of efficiency class C  
and E

Model Identifier WU-M-594-830, 89603216

