

54W / 7360lm / 3000K / On/Off / Diffuse /
2312mm

62581



Design: Eduardo Souto de Moura
 Surface or pendant luminaire with tubular shock-resistant frosted polycarbonate body with 50mm diameter.
 Clear polycarbonate end caps with marked installation angles. Supplied with 30mm plastic cable gland that prevents condensation within luminaire.
 Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
 Power supply included.
 IP67 | IK08 | 230Vac | 50/60Hz



LED 3000K

Light Source **Luminaire**


Power **54W** **63,5W**

Flux **9800lm** **7360lm**

Efficiency **181lm/W** **116lm/W**

LOR - **75%**

UGR - **<28**



Beam angle
Diffuse

Application

Weight
2,3Kg

mm

Finishes

.25 Frost

Mandatory

43702 Surface fitting accessory (>2000mm)

43704 Pendant fitting accessory (>2000mm)

Optional

59061 Stainless steel fitting accessory (>2000mm)

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU

supplemented by 2021/340/EU Energy Consumption Labelling

Ordinance. This product contains light sources of efficiency class C

Model Identifier 28004772

