

Tubo 70

16W / 2020lm / 2700K / On/Off / Diffuse / 1192mm

62608



Design: Eduardo Souto de Moura Surface or pendant luminaire with tubular shockresistant frosted polycarbonate body with 70mm diameter.


Clear polycarbonate end caps with marked installation angles. Supplied with 30mm plastic cable gland that

prevents condensation within luminaire. Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP67 | IK08 | 230Vac | 50/60Hz



2700K	Light Source	Luminaire
Power	16W	19,5W
Flux	2800lm	2020lm
Efficiency	175lm/W	104lm/W
LOR	-	72%
UGR	-	<25



Beam angle Diffuse Application

> Weight 1,4Kg

mm

-30 -1192



Finishes

____.25 Frost

Mandatory

43707 Surface fitting accessory 43709 Pendant fitting accessory

Optional

59058 Stainless steel fitting accessory 59059 Wall fitting accessory

Data according to regulations 2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C Model Identifier 28004771