

Tubo 70

20W / 2575Im / 3000K / On/Off / Diffuse / 1472mm

62626



Design: Eduardo Souto de Moura Surface or pendant luminaire with tubular shockresistant frosted polycarbonate body with 70mm diameter.


Clear polycarbonate end caps with marked installation angles. Supplied with 30mm plastic cable gland that

prevents condensation within luminaire. Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP67 | IK08 | 230Vac | 50/60Hz



● 3000K	Light Source	Luminaire
Power	20W	24,4W
Flux	3575lm	2575lm
Efficiency	179lm/W	106lm/W
LOR	-	72%
UGR	-	<25



Beam angle Diffuse Application

Weight 1,7Kg

mm





Finishes

____.25 Frost

Mandatory 43707 Surface fitting accessory 43709 Pendant fitting accessory

Optional

59058 Stainless steel fitting accessory 59059 Wall fitting accessory

Data according to regulations 2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C Model Identifier 28004772, 28004761