

Tubo 70

16W / 2020lm / 2700K / DALI / Diffuse / 1192mm

62664



Design: Eduardo Souto de Moura Surface or pendant luminaire with tubular shockresistant frosted polycarbonate body with 70mm diameter.


Clear polycarbonate end caps with marked installation angles. Supplied with 30mm plastic cable gland that

prevents condensation within luminaire. Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP67 | IK08 | 230Vac | 50/60Hz



2700K	Light Source	Luminaire
Power	16W	19,5W
Flux	2800lm	2020lm
Efficiency	175lm/W	104lm/W
LOR	-	72%
UGR	-	<25



Beam angle Diffuse Application

> Weight 1,4Kg

mm



Finishes

____.25 Frost

Mandatory 43707 Surface fitting accessory 43711 Pendant fitting accessory

Model Identifier 28004771

Optional 59058 Stainless steel fitting accessory 59059 Wall fitting accessory

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

Data according to regulations 2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C