

Tubo 70

34W / 4400lm / 3000K / On/Off / Diffuse /
1472mm

62675



Design: Eduardo Souto de Moura
Surface or pendant luminaire with tubular shock-resistant frosted polycarbonate body with 70mm diameter.
Clear polycarbonate end caps with marked installation angles. Supplied with 30mm plastic cable gland that prevents condensation within luminaire.
Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP67 | IK08 | 230Vac | 50/60Hz



LED	3000K	Light Source	Luminaire
Power		34W	40W
Flux		6125lm	4400lm
Efficiency		180lm/W	110lm/W
LOR		-	72%
UGR		-	<25




Beam angle
Diffuse

Application



Weight
1,7Kg



Finishes

.25 Frost

Mandatory

43707 Surface fitting accessory
43709 Pendant fitting accessory

Optional

59058 Stainless steel fitting accessory
59059 Wall fitting accessory

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class C
Model Identifier 28004772, 28004761