

Tubo 70

54W / 7200lm / 4000K / On/Off / Diffuse / 2312mm

62693



Design: Eduardo Souto de Moura Surface or pendant luminaire with tubular shockresistant frosted polycarbonate body with 70mm diameter.

Clear polycarbonate end caps with marked installation angles. Supplied with 30mm plastic cable gland that

prevents condensation within luminaire. Fitting accessories ordered separately.


LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP67 | IK08 | 230Vac | 50/60Hz



1000K	Light Source	Luminaire
Power	54W	63,5W
Flux	10000Im	7200lm
Efficiency	185lm/W	113lm/W
LOR	-	72%
UGR	-	<28

-30 -

- Ø70 **-**



Beam angle Diffuse Application Weight 2,6Kg

mm

-30 -

2312

Finishes

____.25 Frost

Mandatory

43708 Surface fitting accessory (>2000mm)

43710 Pendant fitting accessory (>2000mm)

Optional

59062 Stainless steel fitting accessory (>2000mm) 59059 Wall fitting accessory

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class B Model Identifier 28004774