

Tubo 70

41W / 5160lm / 2700K / DALI / Diffuse / 1752mm

63081



Design: Eduardo Souto de Moura Surface or pendant luminaire with tubular shockresistant frosted polycarbonate body with 70mm diameter.


Clear polycarbonate end caps with marked installation angles. Supplied with 30mm plastic cable gland that

prevents condensation within luminaire. Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP67 | IK08 | 230Vac | 50/60Hz



● 2700K	Light Source	Luminaire
Power	41W	48,2W
Flux	7170lm	5160lm
Efficiency	175lm/W	107lm/W
LOR	-	72%
UGR	-	<25



Beam angle Diffuse Application

Weight 1,7Kg

mm





Finishes

____.25 Frost

Mandatory 43707 Surface fitting accessory 43711 Pendant fitting accessory

Optional 59058 Stainless steel fitting accessory 59059 Wall fitting accessory

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

Data according to regulations 2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C Model Identifier 28004771