

24W / 3270lm / 4000K / DALI / Diffuse /
1752mm

63088



Design: Eduardo Souto de Moura

Surface or pendant luminaire with tubular shock-resistant frosted polycarbonate body with 70mm diameter.

Clear polycarbonate end caps with marked installation angles. Supplied with 30mm plastic cable gland that prevents condensation within luminaire. Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included.
IP67 | IK08 | 230Vac | 50/60Hz

LED 4000K

Light Source **Luminaire**


Power 24W 29,3W

Flux 4530lm 3270lm

Efficiency 189lm/W 112lm/W

LOR - 72%

UGR - <25



Beam angle
Diffuse

Application



Weight
1,7Kg

mm

Finishes

.25 Frost

Mandatory

43707 Surface fitting accessory


43711 Pendant fitting accessory

Optional

59058 Stainless steel fitting accessory

59059 Wall fitting accessory

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com



Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains light sources of efficiency class B
Model Identifier 28004774