



Design: O/M + Bartenbach GmbH

Luminaire with housing of aluminium profile with electrostatic 100% polyester paint with textured-finish.

Focal-lens with complex surface and individual complex surface rips to provide a focal point through an aperture for glare free area illumination.

Special springs available on request.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz

**2700K**

**Light Source** **Luminaire**


**Power** **21W** **25,6W**

**Flux** **1800lm** **1320lm**

**Efficiency** **86lm/W** **52lm/W**

**LOR** **-** **73%**

**UGR** **-** **<10**



**Beam angle**  
**Medium 31°**



**Weight**  
**0,55Kg**

**mm**


**26x894**

**Finishes**

- .01 White / RAL 9010**
- .02 Black / RAL 9005**

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com



**Data according to regulations**

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains light sources of efficiency class F  
Model Identifier 4053560342L