

5,6W / 370lm / 4000K / DALI / Medium 40° /
ø60mm

63469



Design: O/M + Bartenbach GmbH
 Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.
 Lightcore optics for defined and perfectly controlled beam of light.
 Easy recessing system with spring clips.

LED CRI>80 / >50.000h, L80/B10
 2-step MacAdam / Power supply included.
 IP20 | 230Vac | 50/60Hz



4000K

Light Source

Luminaire

Power

5,6W

7W

Flux

490lm

370lm

Efficiency

88lm/W

53lm/W

LOR


-

76%

UGR

-

<10



Beam angle
Medium 40°



Weight
0,28Kg

mm

Ø 053

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
 supplemented by 2021/340/EU Energy Consumption Labelling
 Ordinance. This product contains a light source of efficiency class G
 Model Identifier 4053560313H

