One
Square

3,1W / 200lm / 2700K / On/Off / Medium 40° / 45x45mm

63496



Design: O/M + Bartenbach GmbH
Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.
Lightcore optics for defined and perfectly controlled beam of light.
Fitting accessories for different applications are available.

LED CRI>90 / >50.000h, L80/B10
2-step MacAdam / Power supply included.
IP20 | 230Vac | 50/60Hz

LED 2700K	Light Source	Luminaire
Power	**3,1W**	**4W**
Flux	**260lm**	**200lm**
Efficiency	**84lm/W**	**50lm/W**
LOR	**-**	**77%**
UGR	**-**	**<10**



Beam angle
Medium 40°

Application

Weight
0,22Kg

mm

37x37



Finishes

○ **.01** White / RAL 9010
● **.02** Black / RAL 9005

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations
2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class G
Model Identifier 4053560312L

www.om-light.com / mail@om-light.com Rua Maurício Lourenço Oliveira 186, 4405-034 Vila Nova de Gaia, Porto. Portugal. / Apartado 1538 4401-901 Vila Nova de Gaia, Porto Portugal / tel. +351 223 710 419