



One Trimless

5,6W / 430lm / 4000K / On/Off / Flood 56° /
ø54mm

63521




Design: O/M + Bartenbach GmbH
Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.
Lightcore optics for defined and perfectly controlled beam of light.
Recessing accessory supplied separately.

LED CRI>80 / >50.000h, L80/B10
2-step MacAdam / Power supply included.
IP20 | 230Vac | 50/60Hz



	4000K	Light Source	Luminaire
Power	5,6W	7W	
Flux	490lm	430lm	
Efficiency	88lm/W	61lm/W	
LOR	-	88%	
UGR	-	<19	



Beam angle
Flood 56°

Application

Weight

Finishes

- .01 White / RAL 9010**
- .02 Black / RAL 9005**

Mandatory

59039 Trimless accessory (12.5mm ceilings)

155x18mm

59040 Trimless accessory (15mm ceilings)

155x20mm


59041 Trimless accessory (25mm ceilings)

155x30mm

Optional

59083 Removal tool

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com



Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU

supplemented by 2021/340/EU Energy Consumption Labelling

Ordinance. This product contains a light source of efficiency class G

Model Identifier 4053560313H