



One **Square Trimless**

5,6W / 430lm / 4000K / On/Off / Flood 56° / 54x54mm

63547

Design: O/M + Bartenbach GmbH

Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.


Lightcore optics for defined and perfectly controlled beam of light.

Recessing accessory supplied separately.

LED CRI>80 / >50.000h, L80/B10 2-step MacAdam / Power supply included. IP20 | 230Vac | 50/60Hz



1000K	Light Source	Luminaire
Power	5,6W	7W
Flux	490lm	430lm
Efficiency	88lm/W	61lm/W
LOR	-	88%
UGR	-	<19



Beam angle Flood 56°

Application



Weight

Finishes

O .01 White / RAL 9010 ● .02 Black / RAL 9005

Mandatory

59045 Trimless accessory (12.5mm ceilings)

155x18mm

59046 Trimless accessory (15mm ceilings)

155×20mm

59047 Trimless accessory (25mm ceilings)

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class G Model Identifier 4053560313H



mm

