

4,5W / 280lm / 2700K / DALI / Spot 15° /  
ø95mm

63743




Design: O/M + Bartenbach GmbH  
 Ceiling-recessed luminaire with die-cast aluminium body and heat sink.  
 Orientable by 30° on the horizontal axis and 355° on the vertical axis.  
 Reflector built based on micro surfaces with complex geometry coated with aluminium alloy, creating a high-gloss, entirely mirrored surface. Accurate reflector for a defined and controlled beam of light, achieving the maximum efficiency.  
 Reduced height <67mm.  
 Recessing accessory for trimless version supplied separately.

LED CRI>90 / >50.000h, L80/B10  
 2-step MacAdam / Power supply included.  
 IP20 | 230Vac | 50/60Hz



	2700K	Light Source	Luminaire
Power	4,5W	5,8W	
Flux	480lm	280lm	
Efficiency	107lm/W	49lm/W	
LOR	-	58%	
UGR	-	<10	



Beam angle  
 Spot 15°



Weight  
 0,42Kg

mm

Ø 90 (trim version)

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .21 Black+White

Optional

59015 Accessory 12,5mm ceilings (flush installation)  
 150x101x20mm

For the specific supply of "DALI 2" drivers, please contact:  
[support@om-light.com](mailto:support@om-light.com)

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: [support@om-light.com](mailto:support@om-light.com)

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
 supplemented by 2021/340/EU Energy Consumption Labelling  
 Ordinance. This product contains a light source of efficiency class F  
 Model Identifier 2053560245L

