


inVision45 Recessed

23W* / 1360lm* / 2200K-5000K / DALI / Medium 31° / 615mm

63988




Aluminium anodised end caps with electrostatic 100% polyester paint with textured-finish. Housing and perforated cover plate made of aluminium with textured-paint finish. With the latest Bartenbach GmbH technology, inVision45 is a discreet solution, that can use great light distribution and visual comfort from a nearly invisible source. Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. DALI DT8. IP20 | 230Vac | 50/60Hz





2200K-5000K	Light Source	Luminaire
Power	23W*	28W*
Flux	1880lm*	1360lm*
Efficiency	82lm/W	48lm/W
LOR	-	72%
UGR	-	<10
		,



mm ∠Z 47x605



Finishes

O .01 White / RAL 9010 ● .02 Black / RAL 9005

Mandatory 51027 Recessed fitting acessory

O/M recommends that any false ceilings intended for recessed products should be installed only after the products to be used have been chosen. The same applies when preparing openings for this type of product. O/M recommends reinforcing false ceilings close to any such openings, in accordance with the characteristics of the product to be recessed. The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com