

Go

3,7W / 300lm / 2700K / Medium 26° / ø50mm

64732



Design: O/M


Ceiling-recessed luminaire made of aluminium die-

Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10 3-step MacAdam / Power supply not included IP44 | 100mA

₩ (€

2700K	Light Source	Luminaire
Power	3,7W	3,7W
Flux	375lm	300lm
Efficiency	101lm/W	81lm/W
LOR	-	80%
UGR	-	<13




Beam angle Medium 26°

Application



Weight 0.08Kg

@ Ø45 mm



Finishes

O .04 Matt White

• .05 Matt Black

Mandatory

59088 Driver On/Off [100mA]

138×30×21mm

59089 Driver DALI [100mA]

144×30×21mm

59090 Driver PhaseCut [100mA]

122×41×23mm

59091 Driver 1-10V [120mA]

130×30×20mm

Optional

59148 Louvre

ø25x4mm

59149 Elliptical diffuser

The cutout dimensions are for plasterboard ceilings. For other type of $material\ please\ contact: support@om-light.com$

The 5-year guarantee applies only when the luminaire and driver are supplied together.

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F Model Identifier BXRH-27G1000-B-83