

## Go

14W / 7W / 1815Im / 910Im / 2700K / Flood 42° / ø100mm

64761



Design: O/M


Ceiling-recessed luminaire made of aluminium die-

Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10 3-step MacAdam / Power supply not included IP44 | 400mA / 200mA



<b>●</b> 2700K	Light Source	Luminaire
Power	14W / 7W	14W / 7W
Flux	2270lm / 1135lm	1815lm / 910lm
Efficiency	162lm/W	130lm/W
LOR	-	80%
UGR	-	<13




Beam angle Flood 42°

Application



Weight 0.37Kg mm @Ø90



## Finishes

O .04 Matt White

• .05 Matt Black

Mandatory

**59117** Driver On/Off [400mA]

147×43×30mm

**59116** Driver On/Off [200mA]

147×43×30mm

**59119** Driver DALI [400mA]

144×30×21mm

59118 Driver DALI [200mA]

144×30×21mm

**59121** Driver PhaseCut [400mA]

111x22x52mm

**59120** Driver PhaseCut [180mA]

102x49x29mm

**59123** Driver 1-10V [400mA]

163×30×21mm

**59122** Driver 1-10V [200mA]

130×30×20mm

Optional

**59154** Louvre

ø45x4mm

59155 Elliptical diffuser

ø45x4mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

The 5-year guarantee applies only when the luminaire and driver are supplied together.

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class E Model Identifier BXRE-27G20FB-C-83