



10W / 5W / 1215lm / 610lm / 3000K / Spot 20° / ø100mm

64787



Ceiling-recessed luminaire made of aluminium die-


cast.

Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10 3-step MacAdam / Power supply not included IP44 | 300mA / 150mA



3000K	Light Source	Luminaire
Power	10W / 5W	10W / 5W
Flux	1540lm / 770lm	1215lm / 610lm
Efficiency	154lm/W	122lm/W
LOR	-	79%
UGR	-	<10




Beam angle Spot 20°

Application



Weight 0.37Kg mm @Ø90



Finishes

O .04 Matt White

• .05 Matt Black

Mandatory

59109 Driver On/Off [300mA]

147×43×30mm

59108 Driver On/Off [150mA]

147×43×30mm

59111 Driver DALI [300mA]

144×30×21mm

59110 Driver DALI [150mA]

144×30×21mm

59113 Driver PhaseCut [300mA]

102×51×30mm

59112 Driver PhaseCut [150mA]

102x49x29mm

59115 Driver 1-10V [300mA]

130×30×20mm

59114 Driver 1-10V [150mA]

130×30×20mm

Optional

59154 Louvre

ø45x4mm

59155 Elliptical diffuser

ø45x4mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

The 5-year guarantee applies only when the luminaire and driver are supplied together.

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class E Model Identifier BXRE-30G10FB-C-83