




Design: O/M
Ceiling-recessed luminaire made of aluminium die-cast.
Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10
3-step MacAdam / Power supply not included
IP65 | 300mA / 150mA



 4000K	Light Source		Luminaire	
Power	10W / 5W		10W / 5W	
Flux	1555lm / 780lm		1165lm / 585lm	
Efficiency	156lm/W		117lm/W	
LOR	-		75%	
UGR	-		<10	



Beam angle
Spot 20°



Weight
0.37Kg



Finishes

- .04 Matt White
- .05 Matt Black

Mandatory

59109 Driver On/Off [300mA]

147x43x30mm

59108 Driver On/Off [150mA]

147x43x30mm

59111 Driver DALI [300mA]

144x30x21mm

59110 Driver DALI [150mA]

144x30x21mm

59113 Driver PhaseCut [300mA]

102x51x30mm

59112 Driver PhaseCut [150mA]

102x49x29mm

59115 Driver 1-10V [300mA]

130x30x20mm

59114 Driver 1-10V [150mA]

130x30x20mm

Optional

59156 Frosted Glass

ø52x2mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

The 5-year guarantee applies only when the luminaire and driver are supplied together.

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class E
Model Identifier BXRE-40G10FB-C-83