

3,7W / 310lm / 3500K / Medium 26° /
50x50mm

64866



Design: O/M
Ceiling-recessed luminaire made of aluminium die-cast.
Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10
3-step MacAdam / Power supply not included
IP65 | 100mA



LED	3500K	Light Source	Luminaire
Power	3,7W	3,7W	3,7W
Flux	410lm	310lm	310lm
Efficiency	111lm/W	84lm/W	84lm/W
LOR	-	76%	76%
UGR	-	<10	<10




Beam angle
Medium 26°

Application

Weight
0.08Kg



45x45



Finishes

○ .04 Matt White
● .05 Matt Black

Mandatory

59088 Driver On/Off [100mA]
138x30x21mm

59089 Driver DALI [100mA]
144x30x21mm

59090 Driver PhaseCut [100mA]
122x41x23mm

59091 Driver 1-10V [100mA]
130x30x20mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class F
Model Identifier BXRH-35G1000-B-83