


83W / 7990lm / 4000K / DALI / Wide flood
76° / 2984mm

64916




Design: Eduardo Souto de Moura
 Surface luminaire with tubular semi frosted PMMA body with 70mm diameter.
 Clear polycarbonate end caps with marked installation angles.
 Linear lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.
 Equipped with 2m cable (5x0.75 mm²).
 Fitting accessories ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam
 Power supply included.
 IP44 | 230Vac | 50/60Hz



| LED | 4000K | Light Source | Luminaire |
|------------|---------|--------------|-----------|
| Power | 83W | 95,4W | |
| Flux | 11750lm | 7990lm | |
| Efficiency | 142lm/W | 84lm/W | |
| LOR | - | 68% | |
| UGR | - | <19 | |



Beam angle
 Wide flood 76°



Weight

2984 mm

Finishes

.01 White / RAL 9010

Mandatory

59163 Surface fitting accessor (>1600mm)

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
 supplemented by 2021/340/EU Energy Consumption Labelling
 Ordinance. This product contains light sources of efficiency class E
 Model Identifier 4053560084

